

Functions of the Standard Controllers

	R7	3216	3208	B500/ B510	C540/ C550	P570/ P580	3504	H500	H1700	H3700	NCC
Number of programs	1	1		5	10	50	25	20	20	20	100
Segments	1	8		4	20	40	500 ³	20	20	20	20
Extra functions (e. g. fan or autom. flaps) maximum				2	2	2-6	2-8 ³	3 ³	6/2 ³	8/2 ³	16/4 ³
Maximum number of control zones	1	1	1	1	1	3	2 ^{1,2}	1-3 ³	8	8	8
Drive of manual zone regulation				●	●	●					
Charge control/bath control							○	○	○	○	○
Auto tune		●	●	●	●	●	●				
Real-time clock				●	●	●		●	●	●	●
Graphic color display				●	●	●		4" 7"	7"	12"	22"
Graphic display of temperature curves (program sequence)				●	●	●					
Status messages in clear text			●	●	●	●	●	●	●	●	●
Data entry via touchpanel				●	●	●		●	●	●	●
Entering program names (i.e. "Sintering")				●	●	●			●	●	●
Keypad lock				●	●	●	●				
User levels				●	●	●		○	○	○	●
Skip-button for segment jump				●	●	●		●	●	●	●
Program entry in steps of 1 °C or 1 min.	●	●	●	●	●	●	●	●	●	●	●
Start time configurable (e. g. to use night power rates)				●	●	●		●	●	●	●
Switch-over °C/°F	○	○	○	●	●	●	○	●	● ³	● ³	● ³
kWh meter				●	●	●					
Operating hour counter				●	●	●		●	●	●	●
Set point output			○	●	●	●	○		○	○	○
NTLog Comfort for HiProSystems: recording of process data on an external storage medium								○	○	○	
NTLog Basic for Nabertherm controller: recording of process data with USB-flash drive				●	●	●					
Interface for VCD software				○	○	○					
Malfunction memory				●	●	●		●	●	●	●
Number of selectable languages				24	24	24					
Wi-Fi-capable („MyNabertherm“ app)				●	●	●					

¹ Not for melt bath control

² Control of additional separate slave regulators possible

³ Depending on the design

● Standard

○ Option



Mains Voltages for Nabertherm Furnaces

1-phase: all furnaces are available for mains voltages from 110 V - 240 V at 50 or 60 Hz.

3-phase: all furnaces are available for mains voltages from 200 V - 240 V or 380 V - 480 V, at 50 or 60 Hz.

The connecting rates in the catalog refer to the standard furnace with 400 V (3/N/PE) respectively 230 V (1/N/PE).